

CL 75 Secondary Outlet



Assembled View



Exploded View

Multi-Purpose Design with Upstand

RwpClearflow CL 75 Secondary Outlet is a 75mm multi-purpose outlet bowl coupled with the 50mm secondary upstand clamp ring. This outlet can be clamped to any range of roof surface or gutter lining & can be easily adapted to become compatible where outlet welding or a mechanical fixing is Specified. As a secondary, the outlet will operate as a back-up if the water level rises to a depth of 50mm or above.

Performance

RwpClearflow CL 75 has been tested by CRM rainwater to take up to a maximum of 30 l/s during peak storm conditions. During light rain conditions the outlet will operate effectively by gravity, draining a maximum gravity flow of 3.4 l/s.

Material

The RWPclearflow CL75 Secondary Outlet is available in the following materials:

- Stainless Steel 304
- Aluminium

Installation.

Outlets are installed in one of two ways:

Free issue to site.

The main contractor should arrange for a patch of membrane 500mm x 500mm to be issued to RwpClearflow offices. For factory fitting to the rainwater outlets.

Free issue to the gutter supplier for off-site fixing into the gutters.

The outlets are made up loosely and issued to the gutter supplier who fixes them to the gutter under their factory conditions.

Critical dimensions

